

TEGO® Dispers 1010

DESCRIPTION

TEGO® Dispers 1010 is a polymeric wetting and dispersing additive used to disperse pigments in solvents of low polarity, like white spirits. Especially in low polar solvents, its outstanding viscosity reduction can be observed.

KEY BENEFITS

- outstanding viscosity reduction with inorganic particles
- especially for low polarity solvents
- solvent-free, 100% active and liquid

EFFECT

Viscosity reduction with organic pigments/carbon blacks



Color intensity/gloss with organic pigments/carbon blacks



Viscosity reduction with inorganic pigments/fillers



Color intensity/gloss with inorganic pigments/fillers



SUITABILITY

waterborne	solventborne
●	●
radiation-curing	high solids
●	●
direct grind	resin-free pigment concentrates
●	●

● not suitable ● partly suitable ● suitable

TYPICAL APPLICATIONS

- Inkjet Inks
- Pigment concentrates
- Architectural paints

TECHNICAL DATA

acid value (as supplied)	Approx. 15 mg KOH/g
active matter content	100 %
amine value (as supplied)	Approx. 30 mg KOH/g
appearance	liquid
chemical description	high molecular weight polymer

SOLUBILITY

Water	Ethanol
●	●
TPGDA	Butylacetate
●	●
Mineral Spirits	
●	

● not soluble ● partly soluble ● soluble

RECOMMENDED ADDITION LEVEL

As supplied calculated on pigment: 5 - 15 %

PROCESSING INSTRUCTIONS

Add to the grind before dispersion.

HANDLING & STORAGE

When stored in an original unopened packaging between +15 and +40 °C, the product has a shelf life of at least 24 months from the date of manufacture.

MSDS & REGULATORY INFORMATION



This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Operations GmbH | Goldschmidtstraße 100, 45127 Essen, Germany | Telefon +49 201 173-2222 Telefax +49 201 173-1939 | www.coating-additives.com