

# SURFYNOL® DF-220

## DESCRIPTION

SURFYNOL® DF 220 is an effective defoamer concentrate based on mineral oil /wax technology. Silicone-free and contains no fumed silica.

## KEY BENEFITS

- based on mineral oil with good long-lasting defoaming effect
- long-term sustained defoaming
- suitable for medium- to high-PVC formulations

## APPLICATION RECOMMENDATION

### Brush application/roller application



### Airless spraying



### Compressed air spraying



### Flexo/gravure printing



### Dip coating, flow coating, curtain coating



### Flooring



## SUITABILITY

waterborne	solventborne
●	●
2-pack 100%	radiation-curing
●	●
addition to the grinding stage	addition to the let-down stage
●	●

● not suitable ● partly suitable ● suitable

## TYPICAL APPLICATIONS

- Architectural paints
- Printing Inks

## TECHNICAL DATA

active matter content	100 %
appearance	clear colored liquid
chemical description	mineral oil based defoamer
solvent	-

## SOLUBILITY

Water	Ethanol
●	●
TPGDA	Acetone
●	●
Butylacetate	Mineral Spirits
●	●

● not soluble ● partly soluble ● soluble

## RECOMMENDED ADDITION LEVEL

As supplied calculated on total formulation: 0.1 - 1.0 %

## PROCESSING INSTRUCTIONS

Can be introduced in the grind and let-down stage.

## HANDLING & STORAGE

The recommended storage temperature for Surfynol DF-220 defoamer is between 20-30°C. If freezing (white precipitation) occurs, the product should be warmed to approximately 25-40°C and mixed thoroughly to restore it to a homogeneous, clear, pale yellow liquid. This should not adversely affect the product's performance. However, prolonged storage at temperatures above 30°C should be avoided, as this will shorten the shelf life of the product.

## MSDS & REGULATORY INFORMATION



This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Operations GmbH | Goldschmidtstraße 100, 45127 Essen, Germany | Telefon +49 201 173-2222 Telefax +49 201 173-1939 | [www.coating-additives.com](http://www.coating-additives.com)